

SUPER SCREED 100

Cementitious Pre-mixed Floor Screed (30-100mm)

Description

SUPER SCREED 100 is a single component, ready to use pre-mixed cement-based floor screed. It is designed to apply in a thickness between 30-100 mm specially formulated from hydraulic cement, graded aggregates, silica sand, reinforcement fiber and special chemical additives.

SUPER SCREED 100 is ideal for leveling and smoothing uneven floors prior to laying decorative floor coverings, carpets, floor tiles, or any other finishing. It can be applied to most of concrete substrates.

Features & Benefits

- Ready mixed, easy to use just needs to add water at site.
- Low VOC, Eco-friendly.
- Minimize the site errors due to uncontrolled mixing ratios.
- Excellent strength and mechanical properties.
- Provides good adhesion to most substrates.
- Excellent workability.
- Provides superior weather stability.

Uses

SUPER SCREED 100 is used in the following:

- For leveling old or new concrete
- Used to produce bonded, un-bonded and floating screed.
- Leveling and smoothing concrete floors prior to laying of decorative floor finishing; carpets, floor tiles, PVC flooring and parquet.
- Storage and warehouses areas
- Workshops and industrial areas.
- Residential and commercial buildings

Technical Properties

Appearance	Granulated Powder
Color	Grey
Wet Density	2,200 Kg/m ³ approx.

Mixture working time	45 minutes @ 25 °C
Compressive Strength	≥40 N/mm ²
Flexural Strength	≥8 N/mm ²
Shrinkage	0.01%
Water absorption	0.5mm
Open to foot traffic	48 hrs @ 25 °C
Time for tile laying	7 days
Time for receive coating	14 days
VOC	<1.0 g/L

All values are subject to 5-10% tolerance

Standards Compliance

- BS 1201, BS 882 & BS 1881
- BS EN 196-1
- ASTM C 531

Application Procedures

Surface preparation:

Surface should be sound, clean free from loose material, grease, laitance, dirt curing compound, etc.

Bonded screed (thickness from 10 to 50 mm):

Super Screed 100 can be laid as a bonded screed by applying ULTRABOND AR or SBR Slurry to prepare concrete substrate as a bonding and priming layer.

To prepare the slurry primer Mix 1 volume of ULTRABOND AR or SBR to 1 volume of clean water with 3 volumes of fresh cement and mix until a smooth consistency is prepared. Scrub the mixed slurry into the concrete surface; while the slurry is still wet apply Super Screed in order to insure good adhesion with the substrate.

Un-bonded Screed (minimum thickness 50 mm):

Concrete substrates should be neutralized by soaking with clean water prior to screed application. Free water on the surface should be allowed to disperse before application.

Floating Screed (minimum thickness 50 mm):

Place a suitable separating or damp-proof membrane (such as nylon sheet) over the substrate before applying the screed mortar.

Mixing Instructions:

For the preparation of mixture, pour into a container 4-5 liters of water for 50Kg bag of SUPER SCREED 100. Add the powder screed to the water and mix with a low speed electric drill fitted with a suitable paddle, until a uniform, lump free consistency mix is achieved. No further water should be added to the mix. Do not add water to the mix once its start to set.

Application Instructions:

Pour the mixed product onto the surface and spread to the desired thickness using steel trowel or suitable tools. Protect the floor after leveling the mix from direct sunlight, high winds or rain. It is possible to apply flooring material on top of SUPER SCREED 100 (such as ceramic, carpet, etc.) after nearly 7 days (depending on the thickness, the supports humidity and the weather conditions).

Coverage

2.2 m² / 50kg bag at 10mm layer thickness.

Coverage depends on substrate porosity and profile.

Packaging

SUPER SCREED 100 is available in 50kg bags

Storage

Keep the product in dry and sheltered place at temperature between +5°C to +35°C. In these conditions and in closed original containers, the product will have a shelf life of at least 12 months.

Health and Safety

Wear gloves, goggles to avoid any contact with eyes and skin. In case of splashes in the eyes wash abundantly with warm water and consult a doctor.

For further information or particular use, contact SBI Technical Department.

Quality & Care

All products produced in SBI facilities are manufactured under a management system certified to conform to the requirements of the quality and environmental health & safety standards ISO 9001 & ISO 14001.

REV 00-2010

SALES OFFICE : Dubai, Barsha, Rasis Business Center
FACTORY : RAK, Jazerat Al Hamra

Tel.+971 4 3999927
Tel. +971 7 2210066
Fax. +971 7 2433821
P.O.Box 14569
www.sbi-me.com , info@sbi-me.com